



## Optical spectral reshaping for directly modulated 4-pulse amplitude modulation signals

**Ozolins, Oskars; Da Ros, Francesco; Cristofori, Valentina; Pang, Xiaodan; Schatz, Richard; Chaibi, Mohamed E.; Bramerie, Laurent; Popov, Sergei; Galili, Michael; Oxenløwe, Leif Katsuo**

*Total number of authors:*  
12

*Published in:*  
Proceedings of the 19th International Conference on Transparent Optical Networks

*Link to article, DOI:*  
[10.1109/ICTON.2017.8024895](https://doi.org/10.1109/ICTON.2017.8024895)

*Publication date:*  
2017

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*  
Ozolins, O., Da Ros, F., Cristofori, V., Pang, X., Schatz, R., Chaibi, M. E., Bramerie, L., Popov, S., Galili, M., Oxenløwe, L. K., Peucheret, C., & Jacobsen, G. (2017). Optical spectral reshaping for directly modulated 4-pulse amplitude modulation signals. In *Proceedings of the 19th International Conference on Transparent Optical Networks* (pp. 1-1). IEEE. <https://doi.org/10.1109/ICTON.2017.8024895>

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Optical Spectral Reshaping for Directly Modulated 4-Pulse Amplitude Modulation Signals

Oskars Ozolins<sup>1</sup>, Francesco Da Ros<sup>2</sup>, Valentina Cristofori<sup>2</sup>, Xiaodan Pang<sup>1,3</sup>, Richard Schatz<sup>3</sup>, Mohamed E. Chaibi<sup>4</sup>, Laurent Bramerie<sup>4</sup>, Sergei Popov<sup>3</sup>, Michael Galili<sup>2</sup>, Leif K. Oxenløwe<sup>2</sup>, Christophe Peucheret<sup>4</sup>, and Gunnar Jacobsen<sup>1</sup>

<sup>1</sup>ACREO Swedish ICT AB, Kista, Sweden

<sup>2</sup>DTU Fotonik, Technical University of Denmark, Lyngby, Denmark

<sup>3</sup>KTH Royal Institute of Technology, Stockholm, Sweden

<sup>4</sup>FOTON Laboratory, CNRS UMR 6082, ENSSAT, University of Rennes 1, Lannion, France

## ABSTRACT

The tremendous traffic growth in intra/inter-datacenters requires low-cost high-speed integrated solutions [1]. To enable a significantly reduced footprint directly modulated lasers (DMLs) have been proposed instead of large external modulators. However, it is challenging to use DMLs due to their low dispersion tolerance and limited achievable extinction ratio (ER). A promising solution to this problem is optical spectral reshaping (OSR) since it is possible to increase the dispersion tolerance as well as to enhance the achievable ER for both on-off-keying [2] and 4-pulse amplitude modulation (PAM) [3] signals. However, moving to 4-PAM, many of the impressive demonstrations reported so far rely heavily on off-line digital signal processing (DSP), which increases latency, power consumption and cost. In this talk, we report on (i) a detailed numerical analysis on the complex transfer function of the optical filter for optical spectral reshaping in case of pulse amplitude modulation and (ii) an experimental demonstration of real-time dispersion-uncompensated transmission of 10-GBd and 14-GBd 4-PAM signals up to 10- and 26-km SSMF. This is achieved by combining a commercial 10-Gb/s DML with optical spectral shaping, thus removing the need for any complex off-line DSP and improving dispersion tolerance. These achievements are enabled by OSR based on a passive microring resonator fabricated on the SOI platform [4]. Significant improvement in receiver sensitivities was observed for both a 10-GBd signal after 10-km SSMF transmission and 14-GBd with no penalty after 26-km SSMF transmission.

## REFERENCES

- [1] O. Ozolins *et al.*: 100 GHz externally modulated laser for optical interconnects [Invited paper], *J. Lightwave Technol.*, preprint, 2017.
- [2] V. Cristofori *et al.*: Direct modulation of a hybrid III-V/Si DFB laser with MRR filtering for 22.5-Gb/s error-free dispersion-uncompensated transmission over 2.5-km SSMF, in *Proc. ECOC*, Düsseldorf, 2016, paper Th.2.P2.SC4.42.
- [3] C. Yang *et al.*: IM/DD-based 112-Gb/s/lamdba PAM-4 transmission using 18-Gbps DML, *IEEE Photon. J.*, vol. 8, pp. 1-7, 2016.
- [4] F. Da Ros *et al.*: 4-PAM dispersion-uncompensated transmission with micro-ring resonator enhanced 1.55- $\mu$ m DML, in *Proc. CLEO*, California, USA, 2017, submitted.